



Таблица със стойностите на габаритите и присъединителни размери ДРЦ 100, ДРЦ 132, ДРЦД 160 - Изпълнение В3 без фланец

Тип на редуктора	Тип на ел.двигателя	Означение [mm]														
		$\phi d_2$	$d_3 + 0.25$	$b \pm 0.3$	$b_1$	$b_2$	$l_1$	$l_2 \pm 0.3$	$l_3$	$l_4$	$l_5$	$h_1 - 0.5$	$h_2$	$h_3$	$t_2$	$d_5$
GMC 100	MO 63 A-4D	22 j 6	9	130	156	6	50	85	117.5	392	14.5	100	186	15	24.5	M8
GMC 100	MO 63 B-4D	22 j 6	9	130	156	6	50	85	117.5	392	14.5	100	186	15	24.5	M8
GMC 100	MO 71 A-4D	22 j 6	9	130	156	6	50	85	117.5	402	14.5	100	202	15	24.5	M8
GMC 100	MO 71 B-4D	22 j 6	9	130	156	6	50	85	117.5	402	14.5	100	202	15	24.5	M8
GMC 100	T 80 A-4	22 j 6	9	130	156	6	50	85	117.5	447	14.5	100	209	15	24.5	M8
GMC 100	T 80 B-4	22 j 6	9	130	156	6	50	85	117.5	447	14.5	100	209	15	24.5	M8
GMC 132	MO 71 A-6D	32 k 6	14	170	208	10	80	120	165.5	458	24	132	227	25	35.5	M12
GMC 132	MO 71 B-6D	32 k 6	14	170	208	10	80	120	165.5	458	24	132	227	25	35.5	M12
GMC 132	MO 71 B-4D	32 k 6	14	170	208	10	80	120	165.5	458	24	132	227	25	35.5	M12
GMC 132	MO 63 B-4D	32 k 6	14	170	208	10	80	120	165.5	480	24	132	211	25	35.5	M12
GMC 132	T 80 A-6	32 k 6	14	170	208	10	80	120	165.5	523	24	132	234	25	35.5	M12
GMC 132	T 80 A-4	32 k 6	14	170	208	10	80	120	165.5	523	24	132	234	25	35.5	M12
GMC 132	T 80 B-4	32 k 6	14	170	208	10	80	120	165.5	523	24	132	234	25	35.5	M12
GMC 132	T 90 S-4	32 k 6	14	170	208	10	80	120	165.5	529	24	132	257	25	35.5	M12
GMC 132	T 90 L-4	32 k 6	14	170	208	10	80	120	165.5	579	24	132	257	25	35.5	M12
GMC 132	T 100 LA-4	32 k 6	14	170	208	10	80	120	165.5	590	24	132	265	25	35.5	M12
GMC 132	T 100 LB-4	32 k 6	14	170	208	10	80	120	165.5	590	24	132	265	25	35.5	M12
GMCD 160	T 80 B-6	48 k 6	18	205	248	14	110	150	206	590	26	160	260	30	51.5	M16
GMCD 160	T 90 S-6	48 k 6	18	205	248	14	110	150	206	606	26	160	283	30	51.5	M16
GMCD 160	T 80 B-4	48 k 6	18	205	248	14	110	150	206	590	26	160	260	30	51.5	M16
GMCD 160	T 90 S-4	48 k 6	18	205	248	14	110	150	206	606	26	160	283	30	51.5	M16
GMCD 160	T 90 L-4	48 k 6	18	205	248	14	110	150	206	646	26	160	283	30	51.5	M16
GMCD 160	T 100 LA-4	48 k 6	18	205	248	14	110	150	206	667	26	160	291	30	51.5	M16
GMCD 160	T 100 LB-4	48 k 6	18	205	248	14	110	150	206	667	26	160	291	30	51.5	M16
GMCD 160	T 112 M-4	48 k 6	18	205	248	14	110	150	206	667	26	160	301	30	51.5	M16